

ASE-9575-HQ

ASE RESILIENCE



— ASE HEADQUARTERS DOCK —
(supports PTT)



EXTEND YOUR IRIDIUM REACH

EXTEND YOUR IRIDIUM REACH

- ✓ HEADQUARTERS VOICE
- ✓ PTT ENABLED
- ✓ SUPPORTS EXTERNAL SPEAKER FOR CONFERENCE CALLS
- ✓ INTEGRATION WITH OFFICE INFRASTRUCTURE VIA POTS SYSTEM



ALSO AVAILABLE: ASE-9575-BAGDOCK

ASE-9575-BAGDOCK is a battery powered dock that supports both the standard 9575 Extreme and the 9575 PTT. This dock provides communication on the move in a compact, portable package.

WHAT'S IN THE BOX?



ASE-9575-HQ-P

CONTENTS:

fist mic/speaker

docking cradle with POTS support
swivel/desk wall mount
ac/dc adapter



ASE-9575-HQ-H

CONTENTS:

intelligent handset

docking cradle with POTS support
swivel/desk wall mount
ac/dc adapter



ASE-9575-HQ

CONTENTS:

docking cradle with POTS support
swivel/desk wall mount
ac/dc adapter

OPTIONAL ACCESSORIES

← - - - - - →
RECOMENDED FOR PTT SUPPORT

ASE-DA12 ASE-DA20

external antenna
Iridium/GPS



ASE-FA12 ASE-FA20

external antenna
Iridium only *

* no GPS features supported



ASE-MNT03

privacy handset
and mount bracket



ASE-SPK01

external speaker



ASE-9575-HQ

ELECTRICAL SPECIFICATIONS

Operating Voltage	10 - 32 VDC
Power Consumption	12 Watts (Avg Active)
Gain Limit	L1: 26-32 dB FREQ: 1575 ±5 MHZ POL: RHCP BIAS: 3 VDC Cable Impedance: 50 ohm SMA Male

ENVIRONMENTAL SPECIFICATIONS

Operating Temp Range	0°C to +70°C
Exposure	Indoor

MECHANICAL DIMENSIONS

Dimensions	7L x 7W x 5H inches	(18 x 18 x 13 cm)
Weight	2.5 lbs	(1.13kG)
Mounting	Swivel desk/wall mount	

SHIPPING DIMENSIONS

Dimensions	14L x 10W x 6H inches	(36 x 25 x 15 cm)
Weight	5 lbs	(2.27 kG)